

## EQUIPMENT | Punt Design Warli studio

---

| Weaving: handtufted on loom

| Yarn : 50% viscose - 50% linen

| Border: hand hemming

| Backing: cotton canvas or action backing

| Weight / sqm: 5,5 kgs

| Pile height: 15 mms

| Applications: residential use / light contract

| Sizes: any up to 5,5 x 30 mts.

Also suitable as exclusive wall-to-wall carpet.

| Product care: Vacuum regularly. Sweep the carpet surface with a soft broom or vacuum clean it in the direction of the pile. Blot stains immediately, possibly with very little water, dry instantly with white absorbing cloth and hair dryer.

If, after the above treatments, you're not able to remove the stains, or if the rug is placed in heavy traffic public areas, we recommend the service of a professional cleaner.

Linen is not an elastic yarn and will flatten after some time. Viscose shreds during the first few weeks. This is considered to be a normal process.



Class 32 Commercial general  
EN ISO 10874



Luxury class LC5  
EN ISO 1307 (T)  
EN ISO 1425 (T)



Electrical behaviour  
Antistatic floor covering  
EN 14041 (R+L+T)  
EN 1815 (R+L)  
ISO 6356 (T)



Thermal resistance  
EN 14041 (R+L+T)  
EN 1307 (T)  
ISO 8302



Slip resistance  
EN 14041 (R+L+T)  
EN 13893



Reaction to fire  
13501-1



CE mark regulation  
DIR. 89/06/EEC

The above technical and product details were provided at the moment of the publication. Warli reserves the right to modify the materials, dimensions and/or characteristics of its products without prior notice.

